



POS, Accessories, Computers & Tablets Point of Sale

JS-925WS-051

Hardware	Enclosure	Upright
	CPU	Intel® ATOM N270 1.6 GHz
	Chipset	Intel® 945GSE + ICH 7M
	Memory	1 GB DDR2 SO-DIMM . 2 GB Max
	LAN	100BASE-TX/10BASE-T
	Expansion Slot	Touch Panel
	Storage	2.5 inch 160 GB SATA HDD (RAID Capable)
Display	Touch Panel	Yes
	TFT	Yes (Dual Back Light)
	SVGA	12.1" LCD 800 x 600 (SVGA)
	XGA	15" LCD 1024 x 768 (XGA)
System	Supported OS	Windows 7, Windows Vista, Windows XP, WEPOS, Linux kernel 2.6, Slackware Ver. 12.0, POS Ready 2009
Connectivity	Powered USB	-
	Standard USB	USB 2.0 x2
	R-232	x4 D-SUB 9 pin (x2 powered)
	Parallel	-
	VGA	x1 D-SUB 15 pin
	LAN	x1 RJ-45
	Audio	-
	Cash Drawer	x1 RJ type

Environmental conditions	Operating Temperature	+5°C - +40°C
	Operating Humidity	15% RH - 85% RH (no dew)
	Storage Temperature	-30°C - +60°C
	Storage Humidity	10% RH - 90% RH
Dimensions	W x D x H	(incl 15" LCD) W250 mm x D257 mm x H413 mm
Options	2 line Customer Display	Yes
	Magnetic Stripe Reader	Yes
	Fingerprint Reader	Yes
	Dallas Key Reader	Yes
	Customer LCD	-

Copyright © 2014 Panasonic New Zealand